iSense

Wi-Fi Smart Radiator

ECO-Design Lot 20 Compliant

An impressive and forward-thinking smart heating solution!

BEAUTY, POWER AND BRAIN

WITH INSPIRED PERFORMANCE

Wide angle and high sensitivity occupancy detector

Ios/Android Free App

Highly secure cloud

MySense

BENEFITS

- Wi-fi connected through your wireless router without any additional hub
- Remotely-controlled by any mobile device with the MySense free APP
- Full colour user friendly, highly intuitive LCD touch screen with easy to read customisable display
- Discreet extra-flat occupancy detector, dual occupancy detection.
- Auto-programmable with dual optimisation feature
- Permanent settings back-up in case of power failure
- Eco-Design innovation pack, comfort, performance and energy savings

Made in France	Low energy consumption	10 years Warranty	Maintenance Free	Eco Friendly controls	PDI Technology
Real Time energy usage	Presence Detection	Open Window detection	Easy accessible advanced start up Control	Fully compliant with acoustic & visual Legislation	Child protection & rental lock functions

iSense

intelliHeat

£ Cost Efficiency	Energy Efficiency	Can be remotely controlled	2 patented wall-mounting brackets	Help for the visually impaired

The iSense integrates with an advanced smart heating management platform allowing building owners and facility managers to remotely access and control their heating with real-time monitoring and analytical insights. The combination of AI-driven data analytics and remote-control capabilities brings precision and intelligence to heating management, allowing to optimise the heating based on occupancy patterns and prevent unnecessary energy waste when rooms are unoccupied which is cost-effective and environmentally responsible. With precise control, the iSense range is incredibly appealing to modern facilities looking to balance energy efficiency management, ensuring effortless remote control from anywhere. And with a combination of style, innovation and the latest technology, the new iSense range creates a perfect balance of sustainability and comfort to suit any environment.

Touch screen

Features

- Fully controllable revolutionary LCD touchscreen thermostat programmer
- State of the art electronic thermostat accurate to +/ - 0.1˚ C
- Built-in Wi-Fi with intuitive and easy to use app based data analysis software
- Open window detection sensor
- Presence detection with wide range motion sensor
- Weekly Timer Control programmable within the minute
- Auto, Boost, Comfort, Eco, Frost protection, Holiday mode
- Auto-programming with Self Learning process
- Dual optimisation feature
- Energy tariff optimisation
- Child Protection & rental PIN Code Lock functions to avoid accidental changes
- Real time energy consumption monitoring
- 7 Pre-set and customisable programming options
- Geo-location-weather forecast check to heat your home more efficiently and automatically turning the heating on/off when leaving or returning home
- 4 Pre-Set Heating Environments (Commercial, Domestic, Housing, Hotel).
- Web based heating management system for multiple buildings control

Technical Specifications

- Patented automatic lock, easy and quick to install, anti-tilt wall-mounting brackets
- Robust, double insulated Class II anti leakage heating element
- Double coated aluminium body, epoxy paint
- Fully complying with E.N. 60335–1 Acoustic & Visual signals
- Drilling template supplied
- PID control, activated by a Triac with OTA for remote software updates
- Double overheating protection
- Control up to 1000 radiators in different buildings
- NF Electricity Performance *** , IP24, Class II.
- 10 Years Warranty on the aluminium body - 2 years on electronics

MySense

Class 2 / Class II
Double Insulated
Can be used without an earth wire.

CE

EAC
Eurasian Conformity mark
Евразийское соответствие (EAC)

BRITISH STANDARDS

UKCA

CEE Les certificats D'ÉCONOMIES D'ÉNERGIE

RoHS COMPLIANT

Green Product

PRODUCT CODE	WATTAGE	HEIGHT MM	WIDTH MM	DEPTH	WEIGHT KG	PRICE EXCL VAT
I-SEN0750	750	580	509	80	12.5	£ 575
I-SEN1000	1000	580	590	80	14.2	£ 615
I-SEN1250	1250	580	752	80	17.6	£ 640
I-SEN1500	1500	580	832	80	19.5	£ 680
I-SEN2000	2000	580	1075	80	24.4	£ 710